

# UL-LRF-4 Eyesafe Laser Rangefinder



## DESCRIPTION

The UL-LRF-4 laser rangefinder possesses an eyesafe design, compact form factor, lightweight construction, low power consumption, long lifespan, and wide temperature range, among other features. As a result, it is extensively utilized in various applications, such as reconnaissance, surveying, and mapping.

Despite lacking an external shell, this laser rangefinder module comes with a broad selection of interfaces, making it simple to integrate into any system with ease. Additionally, for the convenience of users operating handheld devices and multifunction systems, PC software and communication protocols are also available.


## FEATURES

- Single shot ranging and continuous ranging
- 3-target detection, front and back target indication
- Contain self-checking function
- Wake-on-lan function
- Number of emitted pulses during MNBF  $\geq 1 \times 10^6$  times

## APPLICATIONS

- Handheld devices
- Unmanned aerial vehicle
- Electro-optical pod
- Border surveillance

## PERFORMANCE



# UL-LRF-4 Eyesafe Laser Rangefinder

## SPECIFICATIONS

Parameters	Unit	UL-LRF-4	Comments
Safety Class	-	Class 1	Eye safe
Wavelength	nm	1535±5	—
Max Measuring Range	m	≥4000	Target of 2.3mx2.3m visibility of 8km
Min Measuring Range	m	≤20	—
Range Accuracy	m	±2	Affected by weather conditions and target reflectivity
Measuring Rate	Hz	0.5-10	—
Multiple Targets	-	5	—
Precision	%	≥98%	—
False Alarm Rate	%	≤1%	Probability of occurrence of noise
Dimensions	mm	69x41x30	LxWxH
Weight	g	≤90	—
Data Interface	-	molex-532610771	Other interfaces can be customized
Power Supply	V	5	—
Peak Power Consumption	W	2	Max power consumption when start up
Standby Power Consumption	W	1.2	Function to be shut down by external signal can be customized
Vibration	-	5Hz, 2.5g	—
Shock	-	Axial 100g, 1ms	Can be increased based on user's application scenarios
Operation Temperature	°C	-40~+65	—
Storage Temperature	°C	-55~+70	—

## STRUCTURAL DRAWING (In mm)

